

MANUAL

PROPERTIES

This is a mould and fired product, so the change in tones and the thickness among pieces is a detail which must be understood and accepted. We strongly recommend to mix the pieces from different boxes before installation to avoid the different color zones. This recycled glass mosaic is not recommended for commercial flooring (high traffic).

INSTALLATION

1. Buy at least 10% more of the product for breakages, cuts and a technical reserve.
2. Before applying, make sure that all the boxes have the same identification of quality ,size and hue.
3. Make sure that the wall surfaces are smooth, flat, solid, dry and perfectly clean, we suggest creating a white base about 2mm. Score lines on the surfaces to help the sheet posited correctly. Using the strength of a trowel spread out the adhesive uniformly on the wall. Made sure the adhesive covered the entire surface, one time should be not more than 1m².Must use neutral adhesive. Cement is prohibited. In case there is some excess adhesive on the mosaic, do NOT use acid products to remove it.
4. It is essential to have a clean and dry surface before applying any of these products. You must apply the products in ventilated environments with a temperature higher than 5 °C to achieve an ideal output of these products.
5. Grouting: Allow the adhesive to cure for at least 24 hours before you grout. Using latex knife to fill up any gaps with grout adhesive. After grouting, you may notice a residue or haze on the surface of the mosaic. Simply buff this haze away with a clean soft cloth or sponge. Please pay more attention in grouting and cleaning. because sand or hard residue of adhesives will cause scratch.
6. We recommend the neutral adhesive, for example ones from MAPEI S.P.A, <http://www.mapei.com/>. For light color products, it is prohibited to fill the gaps with dark color adhesive.

MAINTENANCE

1. Use neutral detergent for cleaning.
2. Rinse with clean water and dry the coating with a clean dry cloth.
3. Do not use brushes with steel bristles or any other metal (such as steel sponge). They can scratch, damage or remove glare.
4. Do not use products that contain hydrofluoric acid or muriatic acid in your formulas. They can cause irreversible damage to the product.
5. For daily cleaning, always dry the product after cleaning.
6. We recommend the use of protection products (stain-proof sealer and/or liquid protective wax) to protect the products from the damp and from oils or other liquid stains. It is more recommendable for floor projects.

DISCLAIMER

1. Glass are not guaranteed against scratches and loss of gloss.
2. A product that has been installed is considered as accepted. If there is any defect existing, complain before installation.
3. Recycled glass mosaic may be susceptible to scratch in handling and installation, as well as use. It does not have any guarantee against scratches and loss of shine, especially for those products with a glazed surface which are susceptible to scratches, so special care should be taken when installing tiles. During the installation process, cleaning materials should be used to remove sand from the soles of shoes.
4. The material can present varying shades in different batches.
5. We are not responsible for any complaint due to ignoring the recommendations from this manual.

Pattern Installation Information

Mosaic sheets are directional and will only fit together if installed with guide arrows facing the same way. Directional arrows can be found on the underneath the mosaic pieces between the mesh sheet. See below:

